

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently Amended): A switch device comprising:

a base part;

an operation unit which is to be depressed;

a support section ~~which is~~ provided on the base part, ~~supports a circumferential edge the~~
~~support section supporting a portion around an outer periphery of the operation unit and biases the~~
~~in a manner that~~ at least ~~one~~ a part of the operation unit is movable toward and away from the base
part, ~~said one part of the operation unit lying near the circumferential edge and able to move toward~~
~~and from by the depressing and is biased to be away from~~ the base part ~~when the operation unit is~~
~~depressed and released; and~~

a motion-detecting section ~~which is~~ provided on at least one of the base part and the support
section at a position corresponding to the portion around the outer periphery of the operation unit,
~~is positioned near the circumferential edge of the operation unit and which~~ the motion-detecting
section detecting detects the motion of the circumferential edge portion around the outer periphery
of the operation unit ~~being moved toward the base part when the operation unit is depressed by the~~
depressing,

wherein the support section has a plurality of spring members provided at a position

corresponding to the portion around the outer periphery of the operation unit, the spring members applying a restoring force by an elastic deformation, the restoring force of the spring members constantly biasing the at least a part of the operation unit to be away from the base part.

Claim 2 (Canceled)

Claim 3 (Original): The switch device according to claim 1, wherein the support section has a cushion member which is provided at the circumferential edge of the operation unit and which undergoes elastic deformation when at least one part of the circumferential edge of the operation unit moves toward the base part as the operation unit is depressed.

Claim 4 (Original): The switch device according to claim 1, wherein the support section comprises an operation member which is provided at the base part, which moves toward and from the base part when the operation unit is depressed, which has a shape corresponding to the circumferential edge of the operation unit and supports the circumferential edge thereof, and a biasing section which biases the operation member away from the base part, thereby to bias the operation unit away from the base part.

Claim 5 (Original): The switch device according to claim 4, wherein a motion-detecting section comprises a membrane switch which is provided on the base part, which opposes the operation member and which is closed when the circumferential edge of the operation unit is depressed, and the operation member has semispherical projections which oppose at least the membrane switch.

Claim 6 (Original): The switch device according to claim 4, wherein the biasing section has a plurality of spring members which undergo elastic deformation when the circumferential edge of the operation unit is depressed and which restore shape to bias the operation member away from the base part.

Claim 7 (Original): The switch device according to claim 4, wherein the biasing section has a cushion member, which undergoes elastic deformation when the operation unit moves the operation member toward the base part.

Claim 8 (Currently Amended): The switch device according to claim 5, wherein the support section has an elastic member, which is provided on the semispherical projections of the operation member, which oppose opposes at least the membrane switch.

Claim 9 (Original): The switch device according to claim 5, wherein the biasing section has a cushion member which opposes at least the membrane switch and which undergoes elastic deformation when the operation unit is depressed to move the operation member toward the base part.

Claim 10 (Currently Amended): The switch device according to claim 4, wherein the support section comprises a rotation-detecting section for detecting the rotation of the operation unit, said ~~rotation-detecting~~ support section having a plurality of rollers which rotate around axes extending in radial direction of the operation member and which support the operation unit, allowing the operation unit to rotate in a plane that intersect with the direction in which the operation unit is depressed.

Claim 11 (Original): The switch device according to claim 10, wherein the operation unit has a first gear which is convexo-concave in the rotating direction, and the rotation-detecting section comprises a second gear set in mesh with the first gear and configured to slide in axial direction and a rotation-detecting sensor configured to detect the rotation of the second gear.

Claim 12 (Original): The switch device according to claim 1, wherein the operation unit comprises a top plate which is to be depressed and a projection which protrudes outwardly from the top plate in a circumferential direction the top plate is depressed and which is supported by the

support section.

Claim 13 (Currently Amended): The switch device according to claim 10, wherein the operation unit comprises ~~the~~ a top plate which is to be depressed and the projection which protrudes outwardly from the top plate in the circumferential direction the top plate is depressed, which has a larger diameter than the top plate and which is supported on the rollers of the support section.

Claim 14 (Currently Amended): The switch device according to claim 13, wherein ~~the~~ a projection is shaped like a flange, and the operation unit has an annular member having a cross section bulging downward, said annular member being provided on that surface of the projection, which contact the rollers.

Claim 15 (Original): The switch device according to claim 10, wherein the support section comprises an annular cover in which the operation unit is inserted to move in axial direction and not to move in circumferential direction, which is supported on the base part and which is configured to rotate.

Claim 16 (Original): The switch device according to claim 15, wherein the operation unit has an engagement section, and the annular cover has a fastening section which is configured to position and hold the engagement section in a circumferential direction of the operation unit.

U.S. Patent Application Serial No. 10/645,852
Response filed March 19 2007
Reply to OA dated December 18, 2006

Claim 17 (Original): The switch device according to claim 15, wherein the base part comprises a plurality of rollers which support the annular cover, allowing the same to rotate.

Claim 18 (Currently Amended): The switch device according to claim 1, wherein a force which biases the operation unit away from the base part is substantially equal to a load which the turntable of a record player exerts ~~which~~ when depressed.

Claim 19 (Original): A data-processing apparatus comprising:
a data-reading section, which reads data from a recording medium;
a data-processing section, which processes the data, read from the recording medium;
the switch device of the type defined in claim 1; and
a process control section which changes modes in which the data-processing section processes the data, when the motion-detecting section of the switch device detects that the operation unit is moving toward the base part.

Claim 20 (Original): A data-processing apparatus comprising:
the data-reading section which reads data from a recording medium;
the data-processing section, which processes the data, read from the recording medium;
the switch device of the type defined in claim 10; and

U.S. Patent Application Serial No. 10/645,852
Response filed March 19 2007
Reply to OA dated December 18, 2006

a process control section which changes modes in which the data-processing section processes the data, when the rotation-detecting section of the switch device detects that the operation unit is rotating.

Claim 21 (Original): A playback apparatus comprising:

the data-processing apparatus of the type defined in claim 19; and

a playback section that reproduces data processed by the data-processing apparatus.